

# Medical PC

## A248i6

Specifications



TUV Rheinland tested



# Integrated PC

## A248i-IP65

Also available as  
A248i-IP65 fully IP65  
waterproof model  
for use with H<sub>2</sub>O<sub>2</sub>  
disinfection systems.

Processor	Intel i7 6600U 4MB cache, up to 3.4GHz Intel i5 6300U 3MB cache, up to 3.0GHz
Memory	8GB(max32GB)
Storage	120GB SATA SSD
I/O	2 x USB2.0, 4 x USB3.0 2 x serial, 1 x HDMI, 2 x LAN
Security	Internal (option) smart card, 2D barcode, RFID
WLAN	802.11 ac internal
Display	24inch TFT LED Anti Glare glass
Sizes	557 x 355 x 40 mm
Webcam (option)	2MP
Resolution	1920 x 1080 full HD
Pixel Pitch	0.2715 x 0.2715
Viewing Angle	178 degrees
Active screen area	521.28 (H) x 293.22 (V)
Contrast Ratio	1000 (Typ)
Luminance	300 cd/m <sup>2</sup>
Optical response time	5ms
Enclosure	IP65 front, IPx3 housing waterprotected Anti-bacterial
Power	12V DC medical adapter
Power consumption	29 Watts
Weight	6.7 kg
Touch Screen (option)	Capacitive 10p Multi Touch
Operating temperature	0°C to 40°C
Storage temperature	-20°C to +60°C
Compliance	CE, FCC-B, RoHS, DICOM IEC 60601-1, IEC 60601-1-2, Class 2 double insulation, Energy Star
Operating System	Windows 7, Windows 10
Thin Client compatibility	Citrix, Microsoft, VMware

Dutch Design  
Medical IT of Tomorrow

[www.athena-medical.com](http://www.athena-medical.com)

