

Industrial Touch Display

IVTK-M-191T-G

19" TFT LCD, Capacitive/Resistive Touch Screen, HDMI & VGA , OSD Function Keys



IVTK-M-191T-G is a new industrial touch display. ALAD-191T supports 19 inches 1280*1024 TFT LCD, with 5-wire resistive touch screen, optional projected capacitive touch. There are HDMI&VGA video input, Audio input, 2*3W speakers and DC 9~36V wide power input. It is an industrial-standard multimedia display with a variety of installations that is fit for different applications.

Key Features

- Aluminum die-casting chassis, natural smooth design
- 19" LED TFT LCD, LED backlight
- 5 wire heat-resistant resistive touch screen
- Optional projected capacitive screen, Support multi touch
- HDMI and VGA video input
- Audio input, 2*3W speakers
- DC 9~36V wide power input
- Flat bezel, IP65 front panel



SPEC


Video	HDMI	Resolution	1280*1024
	VGA	Horizontal Frequency	30-90KHz
		Vertical Frequency	56-75Hz
Audio	Frequency Response	±3dB	
	R/L Channel Separation	70dB	
	Degree of Distortion(THD)	1.5~2%	
	Signal-Noise Ratio(S/N)	80dB	
Power	Input Voltage	DC 9~36V	
	Power Consumption	12V@1.8(No consumption output)	
	Power Requirement	> 12V@2.5A	
	Standby Current	Low power consumption , standby consumption<1W	
Audio Amplifier	2*3W(4Ω)(Optional)		
OSD Language	Chinese,English,German,French,Russian,Italian,Spanish,Arabic,and so on		
OSD Function key	AUTO/Power/Menu/Source/UP(LEFT)/DOWN(RIGHT)		
LED Light	Green for display, red for standby		
Mechanical & Environmental	Construction	Aluminum die-casting front bezel and chassis, fin-shaped radiator shell	
	Operating Temperature	-0~60°C with airflow	
	Storage Temperature	-40~80°C	
	Storage Humidity	10~95%@40°Cnon-condensing	
	Shock	10g peak acceleration(duration 11ms)	
	Vibration	1g 5~500Hz	
	Mounting	Panel mounting, VESA 100*100/75*75mm, Rack mounting	
	Dimension	(W*H*D):453.5*388.5*64.1mm ; mounting cut out(W*H) : 445*380mm	
	Net Weight	TBD	
	EMC	CE, FCC Class A	

* All specifications and photos are subject to change without notice.

LCD	Type	19" TFT LED	
	Resolution	1280*1024	
	Color	16.7M	
	Pixel Pitch(mm)	0.294*0.294(mm)	
	Brightness(cd/m ²)	470	
	Viewing Angle	85°(left), 85°(right), 85°(up), 85°(down)	
	Operating Temperature	-0~60°C	
	Backlight Lifetime	50000 hours	
Touch	Type	5 wire resistive screen	Projected capacitive screen
	Resolution	gapless	gapless
	Light Transmittance	83%	90%
	Interface	USB	USB
	Consumption	+5V@300mA	+5V @300mA
	OS	Windows/Linux	Windows/Linux
	Click Lifetime	35 million times	3 billion times

Dimension

Unit: mm



Ordering Info

Model NO.	Introductions
IVTK-M-191T-G/ S001	Industrial touch display, 19" TFT LCD, 5 wire resistive screen, 1*HDMI, 1*VGA, 1*Audio in, 2*speaker, DC 9~36V
IVTK-M-191T(P)-G/ S001	Industrial touch display, 19" TFT LCD, projected capacitive screen, 1*HDMI, 1*VGA, 1*Audio in, 2*speaker, DC 9~36V
IVTK-PA-60DC12	AC/DC power adapter, DC12V/5A 60W